

# SeaShield Glass Outerwrap 70

Protective Fibreglass Outerwrap

**Composition**

SeaShield Glass Outerwrap 70 is a fibreglass cloth impregnated with a water activated resin.

**Uses**

SeaShield Glass Outerwrap 70 is a protective coating which offers exceptional mechanical and impact strength and is used in conjunction with a SeaShield Corrosion Protection System.

**Characteristics**

SeaShield Glass Outerwrap 70:

- Resists hot and cold temperatures,
- Resists water, acid, salts and soil organics,
- Avoids mixing and messy clean-up,
- Contains no solvents,
- Provides a quick, long-term protective coating, and
- Can be applied underwater or to wet surfaces.

**Typical properties**

Colour	Grey	Visual
Flexural strength	110,000 kN/m <sup>2</sup>	ASTM D709-71
Tensile strength	170,000 kN/m <sup>2</sup>	ASTM D638
Compression strength	183,000 kN/m <sup>2</sup>	ASTM D695-77
Setting time		
at 21°C	30 minutes	
at 32°C	15 minutes	

**Application**

see *SeaShield Series 70 Engineering Specification* for additional detail

Application temperature: 0°C to 65°C

**Availability**

SeaShield Glass Outerwrap 70 is available in: 8 inches x 40 ft rolls (200 mm x 12.2 m)

Additional sizes may be available on request

**Storage conditions**

Store in a cool dry place, sealed in original packaging.

SeaShield International pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. SeaShield products are sourced from a company complying with BS EN ISO 9001 Quality Management System.

Revision date: 16/06/2016

SeaShield International  
33-35 Chapel Road,  
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511  
Fax: +44 (0) 20 8761 2456  
Email: [mail@seashield.com](mailto:mail@seashield.com)  
Web: [www.seashield.com](http://www.seashield.com)