

TECHNICAL DATA SHEET

LEADERS IN CORROSION PREVENTION & SEALING TECHNOLOGY



Densyl Mastic Blanket

Mastic preformed as a sheet

Composition

Densyl Mastic Blanket is comprised of a petrolatum compound containing inert siliceous fillers and vegetable fibres. The preformed mastic is backed with a synthetic fibre fabric fully impregnated with petrolatum compound. It contains no volatile solvent.

Uses

Densyl Mastic Blanket is designed as a sheet to ease application to mechanical couplings and flanges to ease the application of Denso corrosion protection tapes.

Service Temperature: -20°C to +70°C

Characteristics

Densyl Mastic Blanket is:

- usable at a wide temperature range,
- is designed as a sheet to ease application, and
- eases wrapping of complex shapes.

Application

See Instructions for use for additional detail.

Recommended primer: Denso Paste or Denso Hi-Tack Primer.

Application Temperature: 0°C to +50°C

Availability

Densyl Mastic Blanket is packed between interleaving film with 3-5 blankets per carton according to dimensions.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Colour	Green/Brown
Specific Gravity	1.39
Thickness	10-12 mm
Weight	14.9 kg/m²
Width	250 mm
Roll Length	1 m

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

> Page **1** of **1** Revision date: 25/10/2022

